

~~TITLE~~

11

Docket #72125

DISTRIBUTOR UNIT FOR LIQUID SUBSTANCES~~+~~

~~DESCRIPTION~~

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a United States National Phase application of International Application PCT/IT2004/000716 and claims the benefit of priority under 35 U.S.C. § 119 of Italian Patent Application FI2003000330 filed December 31, 2003.

5

FIELD OF THE INVENTION

[0002] The present invention relates to a distributor unit for liquid substances utilizable especially, even if not exclusively, as colour unit for printing machines used for executing print on continuous web-shaped material such as tissue paper for the production of kitchen paper rolls, paper napkins, handkerchiefs, toilet paper and the like.

BACKGROUND OF THE INVENTION

[0003] It is known that the printing machines utilized for executing prints of the above mentioned type, also called flexographic printing machines, comprise a drum around which the web travels and at least one cliché cylinder, on which the printing ink is distributed and from which the ink is transferred to the web to be printed. In order to obtain the distribution of the ink on the cliché cylinder, it is used an unit, commonly called "colour unit", comprising a reservoir for the ink or "fountain", a distributor cylinder or "anilox cylinder" which receives the ink from the reservoir and transfers it by contact to the cliché cylinder, and two blades, or doctors, disposed and acting between the fountain and the anilox cylinder.

[0004] In Fig. 1 is represented, schematically, a typical flexographic printing machine with four colour units. In this scheme, (RI) indicates the transmission roll onto which the web (N) to be printed travels, which moves in the direction of the arrow (Z); (C), (D) and (E) indicate three guiding rolls of the web (N) disposed upstream of the roll (RI); (F) and (G) indicate two guiding rolls of the web (N) disposed downstream of the roll (RI); (H), (L), (P) and (Q) indicate four identical colour units symmetrically disposed around the roll (RI); (CD) indicates an anilox cylinder; (CL) indicates a cliché cylinder, (LS) and (LI) indicate two doctors disposed and acting between the fountain (U) and the anilox cylinder (CD); (S) indicates a support structure of the doctors (LS, LI). The two doctors delimitate, in cooperation with the structure (S) and the surface of the anilox cylinder (CD), the fountain (U) in which is contained the ink for the same cylinder (CD). The two opposite bases of the fountain (U) are closed by relevant tight plates or gaskets. (M) indicates the rotation direction of the roll (RI).

5 [0005] _____ The cliché cylinder is constituted by a cylindrical body with smooth surface, onto which ~~it~~there is movably fitted a jacket provided with reliefs ~~act~~acting to form the patterns and the writings to be printed. In such way, for varying the printing effects, it is sufficient to remove the jacket from the cylinder and to substitute it with a different jacket, afterwards called "cliché jacket".

[0006] _____ This operation concerns, mostly, all the colour units of the machine. The latter is stopped during the substitution of the cliché jackets, with a loss of production ~~as higher as greater~~ as corresponding in extent to the time required for the substitution.

10 [0007] _____ In order to substitute of the cliché jacket, it is necessary that the operator dismantles the support of the cylinder utilizing, at least in part, manual tools; this requires a time as ~~greater~~great or as smaller ~~is~~ as the skill of the operator and it can involve risks of damage for the parts which are dismantled and afterwards remounted.

15 [0008] _____ The same drawbacks relates to the distributor units utilized, for example, for distributing glue or other liquid substances on web-shaped materials in movement and structured as the before said colour units, that is provided with a cylinder onto which it is movably fitted a jacket (called also in this case "cliché-jacket" because it is provided with reliefs apt to allow the distribution of the substance only on preset points of the web and not over the whole surface of the same) and a distributor cylinder which receives the substance from a relevant reservoir and, by contact, transfers it to the cliché cylinder.

[0009] _____ Distributor units are described in US 6615716, EP741009 and EP596244.

SUMMARY OF THE INVENTION

[0010] _____ The main object of the present invention is to provide a distributor unit, especially a color unit for printing machines, suitably structured in order to shorten and facilitate the substitution of the cliché-jackets.

[0011] _____ This result has been achieved, according to the invention, by making a distributor unit having the characteristics ~~indicated in claim 1. Further characteristics being set forth in the dependent claims- discussed herein.~~

[0012] _____ The present invention makes it possible to obtain a remarkable reduction of the time required for the substitution of the cliché-jackets, with a correspondent reduction of the loss in the production due to the stop of the machine; this advantage is ~~as~~even more evident with ~~as~~ greater ~~is the~~ number of distributor units involved by this operation.

[0013] _____ Furthermore, a device according to the present invention is relatively simple to be manufactured, it is more easily and more safely usable, and it is reliable also after a prolonged use.

[0014] _____ These and other advantages and characteristics of the invention will be best understood by anyone skilled in the art from a reading of the following description in conjunction with the attached drawings given as a practical exemplification of the invention, but not to be

considered in a ~~limitative sense, wherein: Fig. 1 shows, schematically, limiting sense.~~ The various
features of novelty which characterize the invention are pointed out with particularity in the claims
annexed to and forming a part of this disclosure. For a better understanding of the invention, its
operating advantages and specific objects attained by its uses, reference is made to the
5 accompanying drawings and descriptive matter in which preferred embodiments of the invention
are illustrated.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] _____ In the drawings:

[0016] _____ Fig. 1 is a schematic view showing a typical flexographic printing machine with
10 four colour units;—

[0017] _____ Fig. 2 is a schematic view like ~~to~~ that of Fig. 1, but it refers to a machine provided
with four colour units according to the present invention; —

[0018] _____ Fig. 3 is a schematic view in cross section of the supports of a cliché-cylinder or
roll of a colour unit according to the invention; —

[0019] _____ Fig. 4 is a schematic view in cross section of the supports of an anilox cylinder or
15 roll of a colour unit according to the invention; —

[0020] _____ Fig. 5 is a schematic view in cross section of a colour unit according to the invention, seen from the operator side and in an arrangement of complete rest of the cliché roll on the relevant support on the operator side; =

5 [0021] _____ Fig. 6 represents is a view like to that of Fig. 5, but with the said support shown in a disengaged arrangement; =

[0022] _____ Fig. 7 represents is a sectional view like to that of Fig. 5, but with the colour unit seen from the transmission side; =

[0023] _____ Fig. 8 represents is a view section sectional view like to that of Fig. 6, but with the colour unit seen from the transmission side; =

10 [0024] _____ Fig. 9 represents is a schematic and partial perspective view of the machine of Fig. 2 in operative arrangement, with some, removed parts for a better representation of others; =

[0025] _____ Fig. 10 represents is a view like to that of Fig. 9, with the supports of the cylinders of a colour unit in the arrangement of allowed extraction of a cliché jacket; =

[0026] _____ Fig. 11 represents is a simplified block diagram of the system of control of
15 actuators; = and

[0027] _____ Fig. 12 represents is an enlarged view showing particulars of Fig. 5.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0028] _____ The term "operator side" means the side from which an operator can extract: a cliché-jacket from a corresponding cylinder and substitute it with another cliché-jacket. The

5 term "transmission side" means the opposite side of the machine, that is the side in correspondence of which are positioned the motors which operate the rotation of the cliché-cylinders or rolls and of the anilox rolls or cylinders. The term roll or cylinder means, according to that said above, a cylindrical body with a smooth or substantially smooth surface, onto which a tubular jacket provided with reliefs may be fitted. Said tubular jacket will be called "cliché-jacket"

10 (independently of the fact that the substance to be distributed is ink or other).

[0029] _____ In the enclosed drawings (Figs. 2-12) it there is represented a printing machine with four colour units (1) disposed symmetrically around a transmission cylinder (2) for a web (3) of paper material on which is executed the print. The present machine is also provided with a series of guiding rolls (4) for the web (3), said guiding rolls being disposed upstream and downstream of

15 the cylinder (2), said rolls (4) being associated to a fixed structure (5) which supports also the cylinder (2) and supports, by means of corresponding brackets (6), the colour units (1).

[0030] _____ Each colour unit (1) is disposed on a relevant bracket (6) of the structure (5) and comprises a reservoir (7) or "fountain" for the ink, an anilox cylinder (8) and a cliché cylinder (9) which is disposed adjacent to the transmission cylinder (2), so that the web (3) on which the print

has to be executed results between the cliché cylinder and the transmission cylinder. _As in the conventional systems, the anilox cylinder (8) and the cliché cylinder (9) are associated to corresponding electric motors (10, 11), in order to drive the rotation thereof around the respective longitudinal axis-; said axis are parallel each other and to the rotation axis of the transmission cylinder (2)._ The cliché cylinder (9) is of the type constituted by a cylindrical body with smooth or substantially smooth surface, onto which it is fitted a cliché jacket (18)._ The anilox cylinder (8) receives the ink from the fountain (7) and it transfers the same, by contact, to the cliché cylinder (9) which, in turn, executes a print on the web (3) that travels on the transmission cylinder (2).

[0031] _____ The anilox cylinder (8) and the cliché cylinder (9) have corresponding shafts or axis (12,13) extending both towards the operator side and the transmission side of the machine.

~~Said~~**[0032]** _____ The shafts (12,13) rest on corresponding supports on the operator side (14,15) and. on the transmission side (16,17), mounted on the relevant bracket (6). _More particularly, the shaft (12) of the anilox cylinder (8) rests always on the relevant supports (14) and (16), while the shaft (13) of the cliché cylinder (9) rests on both the supports (15) and (17) only during the printing operation: said shaft (13) being locked in "cantilever" position to the support (17) of transmission side and free on operator side during the extraction and the substitution of the respective cliché jacket (18), as better explained afterwards.

[0033]_____ For blocking the cliché cylinder (9) in cantilever position, can be used, for example, a piston (19) fixed to the support of the same cylinder (9) on the transmission side (17); the stem of said piston is oriented radially with respect to the shaft (13) and is able to lock a sleeve (20) keyed on the rear portion of the shaft (13) of the cylinder (9), that is keyed on the portion of the shaft (13) connected to the motor (11). _When the stem of the piston (19) is extracted, the shaft (13) is locked to the support (17), so that, according to the manner described afterwards, the part of the same shaft on operator side can be unlocked from the support (15) and it is possible to substitute the jacket (18). _In use, or during the printing, the stem of the piston (19) is retracted and the shaft (13) rests on both the relevant supports (15) and (17), free to rotate around its longitudinal axis.

[0034]_____ Both the support on operator side (14) and the support on transmission side (16) of the anilox cylinder (8) are movable on the bracket (6), being mounted on rectilinear guides (21) which are parallel to each other, solid to the bracket (6), orthogonal to the longitudinal axis of the fountain (7), of the anilox cylinder (8) and of the cliché cylinder (9), and on which guides said supports (14,16) are movable thanks to two corresponding screw controls (22) each of which engages, centrally, the base portion of a respective support (14,16) and is operated by an electric motor (23). The rotation of said motors causes the approach of the supports (14,16), and, then, the approach of the anilox cylinder (8) to the cliché cylinder (9) and, vice versa, their spacing. Said motors (23) are solid to said structure (5) and are disposed in correspondence of two heads (50,51) of the same: a motor (23) being disposed on the head on operator side (50), the other motor (23) being disposed on the head on transmission side (51).

10035 Advantageously, according to the invention, the support on operator side (15) of the cliché cylinder (9) comprises two elements (150,151) which, in the normal operative configuration of the machine, that is during the printing, are closed to the cylinder (9), forming a corresponding support on which the shaft (13) of the cylinder (9) is free to rotate around its longitudinal axis. In the configuration of allowed extraction of the cliché jacket (18), with the cliché cylinder (9) in cantilever position (that is locked to the respective support on transmission side 17 by the piston 19), said two elements (150,151) are spaced from the cylinder (9).

10036 According to the embodiment shown in the enclosed drawings, an element (150) of the said support on operator side (15) is connected to the support on operator side (14) of the anilox cylinder (8) and is mounted slidable on the same guides (21), so that the motion of the support (14) determines the motion of the element (150). For example, the connection between said element (150) and the support on operator side (14) of the anilox cylinder (8) can be obtained by connecting, by means of two or more screws (88), a lateral rigid appendix (33) of the element (150) with the support (14), so that a portion (89) of the connecting appendix (33) is in a corresponding receiving seat (346) formed in the support (14). Preferably, said appendix (33) is shaped tubular or cylindrical or prismatic, the relevant portion (89) inside the support (14) is shaped as a flange and the seat (346) of the support (14) which receives the flange (89) has, on the side facing the element (150), a closing frame (34) which prevents the flange (89) to escape. Said frame (150) is fixed to the support (14) by screws (87) and it is in contact with the flange (89). More in particular, the frame (150) is in contact with the surface of the flange which faces the outside of the seat (346), that is facing the element (150).

[0037] In the same seat (346) of the support (14) which receives said flange (89) of the lateral appendix (33) of the element (150), is disposed a spring (345) positioned between the bottom (347) of the seat (346) and the appendix (33).

[0038] The screw (22) which activates the movement of the front support (14) of the anilox cylinder (8) passes, free to rotate around its axis, through an aperture (155) of the element (150). The second movable element (151) of the front support (15) of the cliché cylinder (9) is linked to a corresponding electric motor (24) which is able to operate its translation from and to the cylinder (9) by means of a corresponding screw control (25).

Said [0039] The elements (150,151) define, as said above, the front support (15) of the cliché cylinder (9), forming, by means of respective concavities (156,157) facing the same cylinder (9), two separable rests, diametrically opposed, for a front end flange (90) of the cliché cylinder (9): said flange (90) containing a bearing of the shaft (13) of the cliché cylinder (9). In other words, the front end of the cylinder (9) is provided with a flange (90) which, during the printing, lies on the concavity (157) of the element (150) in cooperation with the element (151) which is in contact with the flange (90) on diametrically opposite side (see Fig. 5). Vice versa, in configuration of release of the front end of the cylinder (9), both the elements (150,151) are spaced from the cylinder (9) (see fig. 6). The spacing of the element (151) from the flange (90) of the cylinder (9) is operated directly by the relevant motor (24). The spacing of the element (150) from the flange (90) of the cylinder (9) is determined by the rearwards motion of the support (14) which is linked to it and which drives it with itself under control of the relevant motor (23).

[0040]_____The support on the transmission side (16) of the anilox cylinder (8) is structurally identical to that on operator side (14).

[0041]_____The support on the transmission side (17) of the cliché cylinder (9) is made by one element, with a tubular appendix (170) facing the cylinder (9); said appendix delimitates a seat for
5 a corresponding portion of the relevant shaft (13) and for said sleeve (20), onto which the stem of the piston (19) pushes when it is necessary to block the cylinder (9) in cantilever position. On opposite side regards to said tubular appendix (170), it is fixed the casing of the motor (11) which operates the rotation of the cylinder (9).

~~Said support~~[0042]_____The support (17) is linked to a corresponding electric motor (177)
10 by means of a screw control (178) in order to allow the motion of the same support along said guides (21) when it is necessary to space the same from the transmission cylinder (2) and, afterwards, for repositioning it in operative configuration.

[0043]_____The supports on the transmission side (16,17) of the anilox cylinder (8) and cliché cylinder (9) are provided, respectively, with an elastic stop (34') and with a rigid stop (33'). Said
15 supports (16) and (17) aren't linked to each other, being independent to each other.

[0044]_____The screw (22), which connects the support on the transmission side (16) of the anilox cylinder (8) with the relevant motor (23), passes, free to rotate around its longitudinal axis, through a respective aperture (67) provided by the support on the transmission side (17) of the

cliche cylinder (9).

[0045]_____The fountain (7) is also mounted movable on said guides (21) for allowing to approach it to the anilox cylinder (8) and to space it when necessary, as provided for the colour units of the conventional printing machines.

5 Said[0046]_____The actuators (10,11, 19,23, 24,177) are connected to a programmable electronic unit (80) of a type known to the technicians of the industrial automation art and, for this reason, not described in detail. _The electronic unit (80), on command by the operator, automatically controls the motions described above and further described afterwards.

10 [0047]_____For extracting a cliche jacket (18) from the cylinder (9) of a colour unit (1) to substitute the jacket extracted with another, with the machine stopped occurs what is described afterwards.

15 [0048]_____The unit (80) activates the piston (19) which, acting on the sleeve (20) keyed on the shaft (13), locks the latter in cantilever position. _In concomitance with this operation, the unit (80) activates the motors (23) which, by means of the screws (22), move backwardly the supports (14) and (16) of the anilox cylinder (8). _The fountain (7) moves backwardly as a consequence of the push exerted on it by the supports (14) and (16)._ The element (150) of the front support (15) of the cliche cylinder (9) is moved by the front support (14) of the anilox cylinder (8) since it is linked to the same. _The element (151) of the support (15) is spaced from the cylinder (9) by

means of the relevant motor (24)._ The support on the transmission side (17) of the cliché cylinder (9) is spaced from the transmission cylinder (2) by the relevant motor (177)._ At this point, the end on the operator side of the cylinder (9) is free, and the cliché jacket (18) can be freely extracted and substituted (in a manner known by the technicians and, therefore, not described in greater detail).

[0049]_____ For repositioning the colour unit in the operative configuration, the unit (80) operates the inversion of the above mentioned movements, and all the supports (14,15, 16, 17) are brought back in their initial positions and arrangements and, afterwards, the piston (19) releases the shaft (13) which, at this point, rests, free to rotate, on the relevant supports on operator and transmission side._ The repositioning of the element (150) of the support (15) in operative arrangement-after the motor (177) has brought back the support (17) in the respective initial position-is determined by the advancement of the support (14) which pushes it toward the cylinder (9) until the re-establishment of the contact between the flange (90) of the latter and the element (151), the position of which constitutes a stop for the unit, and, in particular, for the cliché cylinder (9), travelling toward the transmission cylinder (2). In operative configuration, the elastic stop (34') of the support (16) is compressed on the lateral rigid stop (33') of the support (17) and the spring (345) contained in the support (14) is also compressed, so assuring always the contact between the flange (90) of the cylinder (9) and the element (151).

[0050]_____ Although the preceding description is referred to a colour unit of printing machines, as anticipated, a device according to the present invention is advantageously applicable

to the cases in which the substance to be applied isn't ink but a substance of different type (i.-e. glue, softening liquids or other) to be applied in preset points or zones of a web- shaped material, especially a paper web, by means of a cylinder provided with a cliché jacket movably fitted on it, jacked on which the substance is transferred by means of the contact with a distributor cylinder which receives the substance from a corresponding reservoir. In this case, the reservoir will contain glue, softening substances or other, instead of ink.

[0051] Practically, the construction details may vary in any equivalent way as far as the shape, dimensions, elements disposition, nature of the used materials are concerned, without nevertheless departing from the scope of the adopted solution idea and, thereby, remaining within the limits of the protection granted to the present patent.

[0052] While specific embodiments of the invention have been described in detail to illustrate the application of the principles of the invention, it will be understood that the invention may be embodied otherwise without departing from such principles.

ABSTRACT OF THE DISCLOSURE

A distributor unit includes a reservoir (7) containing a liquid substance, an anilox cylinder (8) and a cliché cylinder (9) onto which is movably fitted a cliché jacket (18), the reservoir (7), the anilox cylinder (8) and the cliché cylinder (9) being movable from and to a cylinder (2) on which travels a web-shaped material (3) which has to receive the substance. The distributor unit has an operator side and a transmission side, the anilox cylinder (8) and the cliché cylinder (9) being held by corresponding supports on operator side (14, 15) and on transmission side (16, 17). A device (19) for locking the cliché cylinder in cantilever position when the corresponding cliché jacket (18) has to be substituted is associated to the support on transmission side (17) of the cliché cylinder (9). The support on operator side (15) of the cliché cylinder (9) includes a first and a second element (150, 151) automatically movable from and to the cliché cylinder (9). The elements in configuration of use hold the cylinder (9) on the operator side and, in a configuration of substitution of the cliché jacket (18), are reciprocally spaced disengaging the operator side of the cliché cylinder (9).